

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
8 July 2004 (08.07.2004)


PCT

(10) International Publication Number
WO 2004/056463 A1

- (51) International Patent Classification⁷: **B01J 8/06**, 8/00, F28F 13/08, F28D 7/16
- (21) International Application Number: PCT/GB2003/005203
- (22) International Filing Date: 3 December 2003 (03.12.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 0216145 19 December 2002 (19.12.2002) FR
- (71) Applicants (for all designated States except US): **BP CHEMICALS LIMITED** [GB/GB]; Britannic House, 1 Finsbury Circus, London EC2M 7BA (GB). **BP CORPORATION NORTH AMERICA INC.** [US/US]; 4101 Winfield Road, Warrenville, IL 60555 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **MAUVEZIN, Mathias** [FR/FR]; Le Venise, Bat C, Quai Alsace Lorraine, F-13500 Martigues (FR). **POULAIN, Christine** [FR/FR]; 18, allée de Barqueroute, F-13620 Carry le Rouet (FR). **RGHIOUI, Mehdi** [MA/FR]; Impasse du Commandant Mandine, Res le Chambord, Bat D, F-13500 Martigues (FR). **TAHERI, Hassan** [US/US]; 229 South Sleight Street, Naperville, IL 60540 (US).
- (74) Agent: **PREECE, Michael**; BP International Limited, Patents & Agreements, Chertsey Road, Sunbury-on-Thames, Middlesex TW16 7LN (GB).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,

[Continued on next page]

(54) Title: PROCESS FOR MANUFACTURING ETHYLENE OXIDE



(57) **Abstract:** The present invention relates to a process for manufacturing ethylene oxide by the catalytic oxidation reaction of ethylene by molecular oxygen in a tube reactor. The reactor comprises a bundle of reaction tubes (5) which are immersed in a heat exchange fluid and filled with a solid silver-based catalyst (8) and which are traversed by a reactive gas current containing ethylene and molecular oxygen, which in contact with the catalyst forms the ethylene oxide. The area of the internal cross-section of the reaction tubes (5) decreases between the inlet (1) and the outlet (3) of the tubes over at least a portion of the length of the tubes and remains constant over any remaining portion. The process makes it possible to increase the selectivity of the reaction to ethylene oxide for a given production of ethylene oxide. It also makes it possible to use a maximum charge of active catalyst per unit of internal tube volume available in the reactor, owing in particular to an optimum heat exchange capable more particularly of supplying a relatively stable reaction temperature profile over the whole length of the reaction tubes and preventing in particular reaction runaways.

WO 2004/056463 A1